

Printing date 25.06.2017

Version number 3

Revision: 25.06.2017

٦

1.1 Product identifier	
	nnovit 5000 liquid
1.2 Relevant identified	l uses of the substance or mixture and uses advised against
No further relevant info	
	substance / the mixture Resin for metallographic testing
• Manufacturer/Supp Kulzer GmbH Leipziger Straße 2, (olier of the safety data sheet olier: 63450 Hanau (Germany) 689-2570 (Wehrheim)
	ent: email: technik.wehrheim@kulzer-dental.com one number: Emergency CONTACT (24-Hour-Number): +49 (0)6132-844
SECTION 2: Hazar	ds identification
	ne substance or mixture
	ording to Regulation (EC) No 1272/2008
Flam. Liq. 2 H225	Highly flammable liquid and vapour.
Skin Irrit. 2 H315	Causes skin irritation.
•	Causes serious eye irritation.
	May cause an allergic skin reaction.
STOT SE 3 H335	May cause respiratory irritation.
· Hazard pictogra	ified and labelled according to the CLP regulation. ms
	>
GHS02 GHS07	7
GHS02 GHS07	
· Signal word Dar	
 Signal word Dar Hazard-determin methyl methacryl 	nger ning components of labelling: late
 Signal word Dar Hazard-determin methyl methacryl triethylen glycol o 	nger ning components of labelling: late limethacrylate
Signal word Dar Hazard-determin methyl methacryl triethylen glycol o Hazard stateme	nger ning components of labelling: late limethacrylate
 Signal word Dar Hazard-determin methyl methacryl triethylen glycol o Hazard statemen H225 Highly flam H315 Causes ski 	nger ning components of labelling: late dimethacrylate nts nmable liquid and vapour. in irritation.
 Signal word Dar Hazard-determin methyl methacryl triethylen glycol o Hazard statemen H225 Highly flam H315 Causes ski H319 Causes sei 	nger ning components of labelling: late dimethacrylate nts nmable liquid and vapour. in irritation. rious eye irritation.
 Signal word Dar Hazard-determin methyl methacryl triethylen glycol o Hazard statemen H225 Highly flam H315 Causes ski H319 Causes sen H317 May cause 	nger ning components of labelling: late dimethacrylate nts mable liquid and vapour. in irritation. rious eye irritation. an allergic skin reaction.
 Signal word Dar Hazard-determin methyl methacryl triethylen glycol o Hazard statemen H225 Highly flam H315 Causes ski H319 Causes sen H317 May cause H335 May cause Precautionary s 	nger ning components of labelling: late limethacrylate nts mable liquid and vapour. in irritation. rious eye irritation. an allergic skin reaction. respiratory irritation. tatements
 Signal word Dar Hazard-determin methyl methacryl triethylen glycol o Hazard statemen H225 Highly flam H315 Causes ski H319 Causes sen H317 May cause H335 May cause Precautionary s P210 Keep 	nger hing components of labelling: late limethacrylate hts mable liquid and vapour. in irritation. rious eye irritation. an allergic skin reaction. an allergic skin reaction. respiratory irritation. tatements b away from heat/sparks/open flames/hot surfaces No smoking.
 Signal word Dar Hazard-determin methyl methacryl triethylen glycol Hazard statemet H225 Highly flam H315 Causes ski H319 Causes se H317 May cause H335 May cause Precautionary s P210 Keep P280 Wea P262 Do re 	nger ning components of labelling: late limethacrylate nts mable liquid and vapour. in irritation. rious eye irritation. an allergic skin reaction. respiratory irritation. tatements o away from heat/sparks/open flames/hot surfaces No smoking. or protective gloves/protective clothing/eye protection/face protection. hot get in eyes, on skin, or on clothing.
 Signal word Dar Hazard-determin methyl methacryl triethylen glycol Hazard statemet H225 Highly flam H315 Causes ski H319 Causes se H317 May cause H35 May cause Precautionary s P210 Keep P280 Wea P262 Do re P243 Take P370+P378 In cause 	nger hing components of labelling: late limethacrylate hts mable liquid and vapour. in irritation. rious eye irritation. an allergic skin reaction. an allergic skin reaction. respiratory irritation. tatements b away from heat/sparks/open flames/hot surfaces No smoking. hr protective gloves/protective clothing/eye protection/face protection.



Printing date 25.06.2017

Version number 3

Revision: 25.06.2017

(Contd. of page 1)

Trade name: Technovit 5000 liquid

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

Description: Product based on methacrylates

 Dangerous components: 		
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-0000	methyl methacrylate Flam. Lig. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-75%
CAS: 2082-81-7 EINECS: 218-218-1 Reg.nr.: 02-2119849716-25	tetramethylene dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 109-16-0 EINECS: 203-652-6 Reg.nr.: 01-2119969287-21-0000	triethylen glycol dimethacrylate Skin Sens. 1B, H317	10-25%
 Additional information For the 	e wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
 - · After inhalation
 - Supply fresh air.
 - Seek immediate medical advice.
 - · After skin contact
 - Instantly wash with water and soap and rinse thoroughly.
 - Seek immediate medical advice.
 - · After eye contact
 - Rinse opened eye for several minutes under running water. Then consult doctor.
 - · After swallowing
 - Rinse out mouth and then drink plenty of water.
 - In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
 - Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
 - For safety reasons unsuitable extinguishing agents Water.
- **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
 - · Protective equipment: No special measures required.
 - · Additional information -

(Contd. on page 3)

GE



Printing date 25.06.2017

Version number 3

Revision: 25.06.2017

Trade name: Technovit 5000 liquid

(Contd. of page 2)

SECTION 6: Accidental release measures
 6.1 Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Avoid contact with eyes and skin.
6.2 Environmental precautions:
Do not allow to enter drainage system, surface or ground water.
Do not allow to enter the ground/soil.
 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).
Do not flush with water or aqueous cleansing agents
6.4 Reference to other sections
No dangerous materials are released.
See Section 8 for information on personal protection equipment.
-
SECTION 7: Handling and storage
7 1 Proceptions for safe handling

7.1 Precautions for safe handling Wear protective equipment. Keep unprotected persons away. Avoid contact with eyes and skin. Keep containers tightly sealed. · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

- Requirements to be met by storerooms and containers: Store in cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
 - Store cool (not above 25 °C).
- Store in cool, dry conditions in well sealed containers.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

	ol parameters	
		s that require monitoring at the workplace:
	ethyl methacrylate	
OES () SI La	hort-term value: 416 mg/m³, ong-term value: 208 mg/m³,	, 100 ppm 50 ppm
· 1	DNELs	
80-62-6 m	ethyl methacrylate	
Dermal	worker industr., l.te., syst.	74.3 mg/Kg/d (human)
Inhalative	worker industr., l.te., syst.	210 mg/m3 (human)
109-16-0 1	triethylen glycol dimethad	crylate
Dermal	worker industr., l.te., syst.	13.9 mg/Kg/d (nd)
Inhalative	worker industr., l.te., syst.	48.5 mg/m3 (nd)
		(Contd. on page 4)



Printing date 25.06.2017

*

Version number 3

Revision: 25.06.2017

Trade name: Technovit 5000 liquid

	(Contd. of page 3)
· PNECs	
80-62-6 methyl meth	nacrylate
freshwater	0.94 mg/l (aqua)
109-16-0 triethylen g	glycol dimethacrylate
marine water	0.0164 mg/l (nd)
	1.85 mg/Kg (nd)
sedim., dw, mar.wat.	
soil,dw	0.274 mg/Kg (nd)
· Additional inf	ormation: The lists that were valid during the compilation were used as basis.
Keep away from Instantly remove Wash hands du Avoid contact we Breathing equ Not neccessar protective mas Protection of If skin contact sensitization. Solvent resista The glove man preparation. Selection of the the degradation Material of The selection further marn preparation calculated in Penetration The exact gloves and For the poly following me Butyl rubbe Fluorocarboo Nitrile rubbe Chloropreme	ctive and hygienic measures m foodstuffs, beverages and food. re any soiled and impregnated garments. uring breaks and at the end of the work. with the eyes and skin. ipment: y with efficient local exhaust. If exposition to vapours is possible, use breathing k (filter A). hands: c cannot be avoided, protective gloves are recommended to avoid possible nt gloves rerial has to be impermeable and resistant to the product/ the substance/ the e glove material on consideration of the penetration times, rates of diffusion and n gloves on of the suitable gloves does not only depend on the material, but also on ks of quality and varies from manufacturer to manufacturer. As the product is a n of several substances, the resistance of the glove material can not be n advance and has therefore to be checked prior to the application. n time of glove material break trough time has to be found out by the manufacturer of the protective has to be observed. ermanent contact of a maximum of 15 minutes gloves made of the materials are suitable: r, BR on rubber (Viton)
SECTION 9: Phy	sical and chemical properties
9.1 Information on to General Informat Appearance: Form:	pasic physical and chemical properties ion Fluid
· Colour:	Colourless

(Contd. on page 5)



Printing date 25.06.2017

Version number 3

Revision: 25.06.2017

Trade name: Technovit 5000 liquid

	(Contd. of page 4
· Smell: · Odour threshold:	Characteristic Not determined.
· pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not determined 101 °C
· Flash point:	10 °C
· Inflammability (solid, gaseous)	Not applicable.
· Ignition temperature:	430.0 °C
 Decomposition temperature: 	Not determined.
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation o explosive air/vapour mixtures is possible.
 Critical values for explosion: Lower: Upper: 	2.1 Vol % 12.5 Vol %
 Steam pressure at 20 °C: 	47.0 hPa
Density at 20 °C Relative density Vapour density Evaporation rate	1.000 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix
· Partition coefficient (n-octanol/wa	ter): Not determined.
 Viscosity: dynamic at 20 °C: kinematic: 9.2 Other information 	50 mPas Not determined. No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

 • 10.2 Chemical stability
 • Conditions to be avoided: No decomposition if used and stored according to specifications. · 10.3 Possibility of hazardous reactions No dangerous reactions known

- 10.4 Conditions to avoid No further relevant information available.
 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

(Contd. on page 6)

GB



Printing date 25.06.2017

Version number 3

Revision: 25.06.2017

Trade name: Technovit 5000 liquid

(Contd. of page 5)

· Acute f	N 11: To	toxicological effects
	oxicity B	ased on available data, the classification criteria are not met.
		es that are relevant for classification:
80-62-6 m		
	LD50	>5000 mg/kg (rat)
	LD50	>5000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat)
		nylene dimethacrylate
Oral	LD50	10120 mg/kg (rat)
109-16-0 t	riethylen	glycol dimethacrylate
Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (mouse)
C • Res May • CMF • C • C • C • C • STO May	Causes sei piratory of cause an R effects (Germ cell Carcinoge Reproduct T-single (cause res T-repeate	The damage/irritation rious eye irritation. allergic skin reaction. (carcinogenity, mutagenicity and toxicity for reproduction) mutagenicity Based on available data, the classification criteria are not met nicity Based on available data, the classification criteria are not met. tive toxicity Based on available data, the classification criteria are not met. tive toxicity Based on available data, the classification criteria are not met. exposure spiratory irritation. ed exposure Based on available data, the classification criteria are not met. are not met.
· STO		
· STO · Asp		
· STO · Asp	N 12: Ec	
STO Asp SECTIOI 12.1 Toxic Aquatic	N 12: Ec tity toxicity:	ological information
STO Asp SECTIOI 12.1 Toxic Aquatio 109-16-0 ti	N 12: Ec ity c toxicity: riethylen	ological information
• STO • Asp • 12.1 Toxic • Aquatic 109-16-0 ti EC50/72h	N 12: Ec sity c toxicity: riethylen > 100 mg	ological information



Printing date 25.06.2017

Version number 3

Revision: 25.06.2017

Trade name: Technovit 5000 liquid

(Contd. of page 6)

SECTION 13: Disposal considerations • 13.1 Waste treatment methods

· Recommendation

Small quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities. • Waste disposal key number: 55370

· Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	1247
 14.2 UN proper shipping name ADR 	1247 METHYL METHACRYLATE MONOME
· IMDG, IATA	METHYL METHACRYLATE MONOMEI STABILIZED, solution
· 14.3 Transport hazard class(es)	
ADR	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	11
 14.5 Environmental hazards: Marine pollutant: 	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number: · EMS Number:	339 F-E,S-D
 14.7 Transport in bulk according to An of Marpol and the IBC Code 	nex II Not applicable.
Transport/Additional information:	



Printing date 25.06.2017

Version number 3

Revision: 25.06.2017

Trade name: Technovit 5000 liquid

· UN "Model Regulation":

(Contd. of page 7)

METHYL METHACRYLATE UN1247, MONOMER, STABILIZED, solution, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3 • 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Relevant phrases H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction.

- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

· Abbreviations and acronyms:

ADDreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) CCE: Lethel accentration 50 percent LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • * Data compared to the previous version altered. GF