

Services to the Sciences Since 1924

CARGILLE LABORATORIES, INC.

55 Commerce Road • Cedar Grove, New Jersey • 07009-1289 USA Phone: 973-239-6633 Fax: 973-239-6096 Email: CargilleLabs@aol.com URL: http://www.cargille.com

CATALOG #16252

IDENTITY (AS USED ON LABEL AND MANUF. LITERATURE)	NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT
CARGILLE IMMERSION OIL TYPE 300	APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.

SECTION 1			
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NUMBER		
CARGILLE LABORATORIES, INC.	WEEKDAY 973 - 239 - 6633 24 HR CHEMTREC 800 - 424 - 9300		
ADDRESS (NUMBER, STREET, CITY, STATE, AND ZIP CODE)	TELEPHONE NUMBER FOR INFORMATION 973 – 239 - 6633		
55 COMMERCE ROAD	DATE PREPARED	SUPERCEDES PRIOR DATED	
	May 23, 2011	MSDS FOR THIS MATERIAL	
CEDAR GROVE, NJ 07009	SIGNATURE OF PREPARER (OPTIONAL)		

THE INFORMATION SUPPLIED IS BASED ON DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION PRESENTED AND CARGILLE LABORATORIES ASSUMES NO RESPONSIBILITY FOR THE RESULTS OF THE USE OF THIS PRODUCT. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RESPONSIBLE FOR ITS USE SHALL MAKE HIS OR HER OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS OR HER PARTICULAR PURPOSE.

CONDITIONS OF INTENDED AND NORMAL USE: (ABBR. C.I.U.) AS A MICROSCOPE IMMERSION OIL AT NORMAL ROOM PRESSURE (760 mm Hg), <u>TEMPERATURE</u> 45 °F TO 104 °F IN A NON MISTED / NON AIRBORN STATE IN A ROOM HAVING NORMAL AIR CHANGES, (2) / HR., IN A TRAINED AND SUPERVISED LABORATORY / INDUSTRIAL SETTING USING STANDARD GL / GM PROCEDURES. SEE SECTIONS 7 AND 8

SECTION 2 - HAZARDOUS INGREDIENTS SPECIFIC CHEMICAL IDENTITY INFORMATION					
HAZARDOUS COMPONENTS	(COMMON NAME (S))	OSHA PEL CEILING	ACGIH TLV T.W.A.	OTHER LIMITS RECOMMENDED	% (OPTIONAL)
TRADE SECRET	HYDROGENATED TERPHENYL	N.E.	5 mg / CUBIC METER *		
TRADE SECRET	TERPHENYL	5 mg / CUBIC METER *	5 mg / CUBIC METER *		
TRADE SECRET	NATURAL HYDROCARBONS	5 mg / CUBIC METER *	5 mg / CUBIC METER *	IF MISTED	
TRADE SECRET	POLYBUTENES	5 mg / CUBIC METER *	5 mg / CUBIC METER *	IF MISTED	

*PEL CEILINGS & TLV T.W.A.S IF ANY SHOULD NOT OCCUR IF C.I.U. AND SECTIONS 7 & 8 FOLLOWED.

NOTE: PRODUCT NORMALLY SOLD IN 1/4 OZ. TO 1 GALLON QUANTITIES. USED IN SINGLE DROP TO A FEW CUBIC CENTIMETERS PER APPLICATION. SEE REQUISITIONER FOR SPECIFIC QUANTITIES INVOLVED.

SECTION 3 - PHYSICAL / CHEMICAL CHARACTERIS	1103		
BOILING POINT AT 760 mm Hg		SPECIFIC GRAVITY ($H_2O = 1$) TEMP. 23 °C / 73 °F	
340 °C	644 °F		.9
VAPOR PRESSURE IN MM Hg (TEMP.)		MELTING POINT	
73 °F	< 0.1		< 32 °F
VAPOR DENSITY (AIR = 1) AT (mm Hg & TEMP.)		EVAPORATION RATE AT 760 mm Hg & 23 °C / 73 °F	
760 73 °F	ca 1	(MINERAL OIL = 1)	ca 1
SOLUBILITY IN WATER AT (MM Hg & TEMP.)		APPEARANCE AND ODOR	
760 73 °F	NIL	LIGHT YELLOW, SLIGHT CHARACTERISTIC ODOR	

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA						
FLASH POINT (CUP METHOD USED)	FLAMMABLE LIMITS	LEL	UEL			
> 325 °F (163 °C) C.O.C.		N.D.F.	N.D.F.			
EXTINGUISHING MEDIA						
CARBON DIOXIDE, FOAM, DRY CHEMI	CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR ANY CLASS B AGENT.					
SPECIAL FIRE FIGHTING PROCEDURES						
NONE						
UNUSUAL FIRE AND EXPLOSION HAZARDS						
NONE						

ABBREVIATIONS: N.A. = NOT APPLICABLE; N.D.F. = NO DATA FOUND; TR.S. = TRADE SECRET; N.E. = NOT ESTABLISHED; C.I.U. = CONDITIONS OF INTENDED USE; < = LESS THAN; > = GREATER THAN.

SECTION 5 - REACTIVITY DAT	ΓΑ	•				
STABILITY	UNSTABLE		4			
	STABLE	YES				
INCOMPATIBILITY (MATERIALS A			,			
		RONG	DXIDIZERS, HEAT A			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO A	UD		
POLYMERIZATION	WILL NOT OCCUR					
	WILL NOT OCCOR	х	NONE			
SECTION 6 - HEALTH HAZAR	DATA	^	HOILE			
ROUTE (S) OF ENTRY:	INHALATION	2	SKIN?	MUCOUS	MEMBRANES / EYES?	INGESTION?
(NOT LIKELY AT C.I.U.)	YES	!	SKIN ? SLIGHT	MUCOUS	SLIGHT	POSSIBLE
HEALTH HAZARDS (ACUTE AND			3610111		SLIGITI	FUSSIBLE
	/		OWN AT C.I.U.			
CARCINOGENICITY LISTED:	NTP?		IARC MON	IOGRAPHS?	C	SHA CARCINOGEN?
	NO			NO		NO
SIGNS AND SYMPTOMS OF EXPO	SURE					
OILY FEEL, I	F LIQUID IS MISTED O	r abov	e 150 °F (NOTAC.	I.U.) HEADACHES AN	ND NAUSEA POSSIBLE.	
MEDICAL CONDITIONS GENERALI	LY AGGRAVATED BY E	XPOSU	RE			
	N.)	D.F.				
EMERGENCY AND FIRST AID PRO	CEDURES: INCLUDE	POSSIE	BLE MATERIAL THAT	MAY HAVE BEEN MIX	ED WITH LIQUID DURING	G USE.
INHALATION – (NOT LIKELY AT	C.I.U.) IF CONCERN	ARISES	REMOVE TO FRESH	I AIR.		
· · · · · · · · · · · · · · · · · · ·						
SKIN & CLOTHES - PROMPT SO	AP AND WATER WASH	1.				
EYES - FLUSH WITH WATER, SI	LIGHT TEMPORARY IR	RITATIC	ON POSSIBLE (CONS	SULT PHYSICIAN).		
		0014411				
INGESTION - LOW ORDER OF T	UXICITY, FIRST AID N	ORMALI	INOT NEEDED (CO	JNSULT PHYSICIAN)	•	
SECTION 7 - PRECAUTIONS F	OR SAFE HANDLING	AND US	E – FOLLOW C.I.U.	SEE SECTION 1		
STEPS TO BE TAKEN IN CASE MA	TERIAL IS RELEASED	OR SPIL	LED			
ABSORB, PLACE IN PL	ASTIC (POLYETHYLE	NE OR	POLYPROPYLENE)	ONTAINER, CAP OR	TWIST TIE CLOSURE (SEE SECTION 8).
WASTE DISPOSAL METHOD:						
			ST BE IN ACCORDAN	CE WITH CURRENT L	OCAL, STATE, AND FED	ERAL REGULATIONS.
PRECAUTIONS TO BE TAKEN IN H	IANDLING AND STORIN	NG		0-		- 0)
			STORE BI	ETWEEN 65 °F AND	90 °F (18 °C AND 3	2°C)
OTHER PRECAUTIONS						
	AVOID CONTI	INUAL L	IRECT SUNLIGHT, V	APORIZING OR ATOM	IIZING.	
SECTION 8 - CONTROL MEAS			NDED (SEE SECTIO	1)		
RESPIRATORY PROTECTION (SF	-					
	SEE "VENTIL	ATION"				
VENTILATION	LOCAL EXHAUST				SPECIAL	
-			*			I.A.
F	MECHANICAL (GENER	RAL)			OTHER	
		,,	*			I.A.
PROTECTIVE GLOVES				EYE PROTECTION		
	SURGICAL TYPE, IF V	VORN			*	
OTHER PROTECTIVE CLOTHING (OR EQUIPMENT					
			*			
* = NOT MANDATORY I	EXCEPT AS GOOD LAF	BORATC	RY INDUSTRIAL PRA	CTICES.		
					YGIENE, USE OF CHEM	ICAL LAB APRON
	GLES, AVOIDANCE OF					-
SPECIAL PRECAUTIONS	,	27				
			N.A.			
			-			