

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: PolarStat Plus™ Yellow

Product Number: PSP-12Y

Product Description: PolarStat Plus Yellow Embedding Medium

Synonyms: Frozen Section Media

Intended Use of the Product

Frozen sections. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

StatLab Medical Products
 2090 Commerce Drive
 McKinney, TX 75069
 800-442-3573
 972-436-1369 Fax
www.statlab.com

Emergency Telephone Number

Emergency number : CHEMTREC 800-424-9300 (USA & Canada)
 CHEMTREC 703-527-3887 (International)
 Non-transport 972-436-1010 (USA)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Not classified

Label Elements

GHS-US Labeling

No labeling applicable

Other Hazards

No additional information available

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Polyvinyl alcohol	(CAS No) 9002-89-5	< 10	Combustible Dust
Polyethylene glycol	(CAS No) 25322-68-3	4	STOT SE 3, H335
1-Tetradecanaminium, N,N,N-trimethyl-, bromide	(CAS No) 1119-97-7	< 1	Acute Toxicity 4 (Oral), H302 Skin Irritation 2, H315 Eye Damage 1, H318 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400
Methyl alcohol	(CAS No) 67-56-1	< 0.1	Flammable Liquid 2, H225 Acute Toxicity 3 (Oral), H301 Acute Toxicity 3 (Dermal), H311 Acute Toxicity 3 (Inhalation:vapor), H331 STOT SE 1, H370

Full text of H-phrases: see section 16

PolarStat Plus™ Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Assure fresh air breathing. If you feel unwell, seek medical advice.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: None expected under normal conditions of use.

Inhalation: None expected under normal conditions of use.

Skin Contact: May cause skin irritation.

Eye Contact: May cause eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Powder, alcohol-resistant foam, water spray, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen compounds.

Reference to Other Sections Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

PolarStat Plus™ Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s)

Frozen sections. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Methyl alcohol (67-56-1)		
Mexico	OEL TWA (mg/m ³)	260 mg/m ³
Mexico	OEL TWA (ppm)	200 ppm
Mexico	OEL STEL (mg/m ³)	310 mg/m ³
Mexico	OEL STEL (ppm)	250 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
Alberta	OEL STEL (mg/m ³)	328 mg/m ³
Alberta	OEL STEL (ppm)	250 ppm
Alberta	OEL TWA (mg/m ³)	262 mg/m ³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	250 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	250 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m ³)	328 mg/m ³
New Brunswick	OEL STEL (ppm)	250 ppm
New Brunswick	OEL TWA (mg/m ³)	262 mg/m ³
New Brunswick	OEL TWA (ppm)	200 ppm
Newfoundland & Labrador	OEL STEL (ppm)	250 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	250 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m ³)	328 mg/m ³
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OEL TWA (mg/m ³)	262 mg/m ³
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (mg/m ³)	328 mg/m ³
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OEL TWA (mg/m ³)	262 mg/m ³
Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	250 ppm
Ontario	OEL TWA (ppm)	200 ppm

PolarStat Plus™ Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Prince Edward Island	OEL STEL (ppm)	250 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m ³)	328 mg/m ³
Québec	VECD (ppm)	250 ppm
Québec	VEMP (mg/m ³)	262 mg/m ³
Québec	VEMP (ppm)	200 ppm
Saskatchewan	OEL STEL (ppm)	250 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m ³)	310 mg/m ³
Yukon	OEL STEL (ppm)	250 ppm
Yukon	OEL TWA (mg/m ³)	260 mg/m ³
Yukon	OEL TWA (ppm)	200 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide sufficient ventilation to keep vapors below permissible exposure limit. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, Colorless; Gel like
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting/Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density/Specific Gravity	: Not available
Solubility	: Soluble in water
Partition coefficient: n-octanol/water	: Not available
Viscosity	: 3500 - 5500 cps

PolarStat Plus™ Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact.

Explosion Data – Sensitivity to Static Discharge : Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Nitrogen compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: None expected under normal conditions of use.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged skin contact may cause dermatitis and defatting.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

1-Tetradecanaminium, N,N,N-trimethyl-, bromide (1119-97-7)	
LD50 Oral Rat	390 mg/kg
Polyethylene glycol (25322-68-3)	
LD50 Dermal Rabbit	> 20 ml/kg
Polyvinyl alcohol (9002-89-5)	
LD50 Oral Rat	> 20 g/kg
Methyl alcohol (67-56-1)	
ATE US (oral)	100.00 mg/kg body weight
ATE US (dermal)	300.00 mg/kg body weight
ATE US (vapors)	3.00 mg/l/4h

Carcinogenicity

Polyvinyl alcohol (9002-89-5)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Methyl alcohol (67-56-1)	
LC50 Fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

PolarStat Plus™ Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Persistence and Degradability Not available

Bioaccumulative Potential

Methyl alcohol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

14.1. UN Number Not regulated for transport

14.2. UN Proper Shipping Name Not regulated for transport

14.3. Additional Information Not regulated for transport

Transport by Sea Not regulated for transport

Air Transport Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

1-Tetradecanaminium, N,N,N-trimethyl-, bromide (1119-97-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Polyethylene glycol (25322-68-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Polyvinyl alcohol (9002-89-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Methyl alcohol (67-56-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
SARA Section 313 - Emission Reporting	1.0 %
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

US State Regulations

Methyl alcohol (67-56-1)	
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
Polyethylene glycol (25322-68-3)	
U.S. - Minnesota - Hazardous Substance List	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Polyvinyl alcohol (9002-89-5)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Methyl alcohol (67-56-1)	
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)	

PolarStat Plus™ Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Connecticut - Volatile Substances
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - Skin Designations
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour

PolarStat Plus™ Yellow

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
 U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
 U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
 U.S. - Tennessee - Occupational Exposure Limits - Skin Designations
 U.S. - Tennessee - Occupational Exposure Limits - STELs
 U.S. - Tennessee - Occupational Exposure Limits - TWAs
 U.S. - Texas - Effects Screening Levels - Long Term
 U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - Skin Designations
 U.S. - Vermont - Permissible Exposure Limits - STELs
 U.S. - Vermont - Permissible Exposure Limits - TWAs
 U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
 U.S. - Washington - Permissible Exposure Limits - Skin Designations
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs

Canadian Regulations

PolarStat Plus™ Yellow

Uncontrolled product according to WHMIS classification criteria

1-Tetradecanaminium, N,N,N-trimethyl-, bromide (1119-97-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Polyethylene glycol (25322-68-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Polyvinyl alcohol (9002-89-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Methyl alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

IDL Concentration 1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 06/04/2017

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Toxicity 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Toxicity 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Toxicity 3 (Oral)	Acute toxicity (oral) Category 3
Acute Toxicity 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Combustible Dust	Combustible Dust
Eye Damage 1	Serious eye damage/eye irritation Category 1
Eye Irritation 2A	Serious eye damage/eye irritation Category 2A
Flammable Liquid 2	Flammable liquids Category 2
Skin Irritation 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2

PolarStat Plus™ Yellow

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
Combustible Dust	May form combustible dust concentrations in air
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

NFPA Health Hazard : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

NFPA Fire Hazard : 1 - Must be preheated before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Party Responsible for the Preparation of This Document

StatLab Medical Products

Phone Number: 800-442-3573

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS